



TECHNICAL INFORMATION: SY 750 ECC/5/R1

**ECO-FRIENDLY EASY CLEAN PAINT**

## SYLPYL 750 ECC ELITE PLUS



Acrylic Easy Clean Paint (Interior & Exterior)

COMMERCIAL NAME: **DECORPLASTIC ECC ELITE PLUS**

### GENERAL INFORMATION

**SYLPYL 750 ECC** falls slightly above the middle of the price range of architectural paints (ASTM D5146-10), with a very high performance characteristics, compared to the high of price range of architectural paints. This product is formulated with a potent additive that provides excellent initial and long lasting water beading as well as weather and moisture resistance. So you can easy clean your interior and exterior surfaces. Experts and contractors say that while price doesn't always correlate with quality – some of the best exterior paints fall slightly above the middle of the price range – you should steer clear of bargain-priced paints as they don't weather as well as the premium products.

Since it is an acrylic paint, it is a popular choice due to its low odor. Many people find they are bothered by the scent of other paints, especially oil paints. This acrylic paint is water based, but becomes water resistant when dry. It may be used to seal and protect all kind of surfaces, and will adhere to almost any material. This paint dries incredibly quickly compared to the drying time of the high cost 100% acrylic paints. It has an excellent durability and hide. Provides a high resistance to peeling, blistering and is formulated with a potent mildew-resistant additive to avoid premature stains even in humid tropical areas.

Suitable for application on concrete, stucco, gypsum, gypsum boards, drywall, stone, vinyl, aluminum, metals, windows, doors, shutters, trim, garage doors, outdoor furniture, iron and railing.

**SYLPYL 750 ECC** is a very versatile and economy conscious 100% acrylic paint. Its satin stylish appearance, gives a very elegant texture for an outstanding architectural finish, special for interior and exterior walls, ceilings and exterior of buildings in general. In new surfaces apply first one coat of our primer-sealer SYLPYL 77 to highly improve coverage.

### PRODUCT SPECIFICATIONS

**PRODUCT:** SYLPYL 750 ECC ELITE PLUS.

**TYPE:** Acrylic water based.

**COLOR:** White and machine wide range of colors.

**SHEEN:** Satin (20-35 U.B.@85°). It can be manufactured in flat (matt) by special request.

**SOLIDS BY VOLUME %:** 35-43

**VISCOSITY:** 110-125 KU

**DENSITY:** 1.30-1.38 G/ML

**WASHABILITY:** More than 10,000 cycles.

**THEORETICAL COVERAGE:** 14 square meters per liter at 1 mil.

**PRACTICAL COVERAGE IN SQUARE METERS PER LITER FOR TWO COATS:**  
5-6 square meters per liter. This coverage can be more or less, depending on the roughness of the surface and the method of application.

#### COVERAGE GUIDE:

**TYPE OF  
SURFACE**

Smooth  
Textured  
Rough

**FINAL THICKNESS 2 COATS\*  
SYLPYL 715 ECC**

10-12 square meters per liter  
6-8 square meters per liter  
3-5 square meters per liter

\*Depending the color tone and type of surface

**NUMBER OF COATS RECOMMENDED:** TWO.

**OVER POROUS SURFACES SUCH AS CONCRETE:** We recommend to apply one coat of Sylpyl 77 primer-sealer to improve coverage. If no sealer is used in new surfaces, apply three coats.

**THINNER:** Clean water. Max 10%.

**DRYING TIME AT 77°F (25°C):**

**TO TOUCH:** 30 Minutes.

**HARD:** 60 Minutes.

**TO RECOAT:** 120 Minutes.

**SURFACE PREPARATION:** Fill cracks, pits and voids with patching Mortar. Remove dirt, grease, mildew, loose rust, peeling paint or other contamination to ensure good adhesion. Glossy surfaces: Lightly sand to a dull finish. Unpainted plasterboard, brick or cement: Apply One coat of Sylpyl 77 water based all-in-one Vinyl Acrylic interior/exterior primer/sealer/undercoat with excellent hiding power. Surface must be dry.

**APPLICATION METHOD:** Roller, brush, conventional spray and airless.

**SHELF LIFE AT 77°F (25°C):** Minimum 12 months in closed containers.

**PACKAGING:** 1, 4 and 19 liter containers.

1 Liter=0.264 US gallon 1 square meter=10.7639 square feet

R1/JGAF

THE RECOMMENDATIONS MADE HEREWITH AND THE INFORMATION SET FORTH WITH RESPECT TO THE PERFORMANCE OR USE OF OUR PRODUCTS ARE BASED ON OUR OWN RESEARCH, FROM LABORATORY TESTS WHICH ARE BELIEVED, BUT NOT WARRANTED, TO BE ACCURATE. THE PRODUCTS DESCRIBED ARE SOLD, WITHOUT WARRANTY, AS TO FITNESS OF PERFORMANCE, EXPRESSED OR IMPLIED, AND UPON CONDITION THAT PURCHASERS SHALL MAKE THEIR OWN TESTS TO DETERMINE THE SUITABILITY OF SUCH PRODUCTS FOR THEIR PARTICULAR PURPOSES. LIKEWISE, STATEMENTS CONCERNING THE POSSIBLE USES OF OUR PRODUCTS ARE NOT INTENDED AS RECOMMENDATIONS TO USE OUR PRODUCTS IN THE INFRINGEMENT OF ANY PATENTS OR THE INDORSEMENT OF PRODUCTS OF SPECIFIC MANUFACTURERS. WE DO NOT ASSUME ANY LIABILITY OR RESPONSIBILITY OF THE PRODUCT RELATIVE TO COVERAGE, PERFORMANCE, INJURY OR DAMAGE RESULTING FROM IT'S USE. PRODUCT INFORMATION MAY CHANGE WITHOUT PREVIOUS NOTICE.

Av. Desierto de los Leones N° 5429 Col. Alcantarilla, Deleg. Alvaro Obregón, 01720 México City Tel:(5255) 54252366 Fax: (5255) 54252365

E-mail: [sylpyl@sylpyl.com.mx](mailto:sylpyl@sylpyl.com.mx) ISO-9001-2008 & ISO 14001-2004 Certified Company. Visit us at: [www.sylpyl.com.mx](http://www.sylpyl.com.mx)