



TECHNICAL INFORMATION: SYL 750 Syl HBE PRIMER/RA/JGBC/HBP

## ECO-FRIENDLY PAINT

# SYLPYL 750 HBE PRIMER

Acrylic (Interior & Exterior) High Build PRIMER-SEALER

COMMERCIAL NAME: DECORPLASTIC 750 HBE PRIMER

## GENERAL INFORMATION

**SYLPYL 750 DECORPLASTIC HBE PRIMER** is in the range of low priced high-quality high build architectural primer-sealer, with very good performance characteristics that its main goal is to improve top coat performance and finish. This primer ensures the finish coat appearance is smoother with a uniform sheen that also fills rough surfaces and uneven new drywall. It helps to fill pores, pinholes and cover minor drywall damages and sanding grooves.

Since it is an acrylic primer, it is a popular choice due to its low odor. Many people find they are bothered by the scent of other paints, especially oil paints. This acrylic paint is water based but becomes water resistant when dry. It may be used to seal and protect all kind of surfaces and will adhere to almost any material. This paint dries incredibly quickly compared to the drying time of the high cost of other acrylic paints. It has an excellent durability and hide. Provides a high resistance to peeling, blistering and is formulated with a potent mildew-resistant additive to avoid premature stains even in humid tropical areas.

Suitable for application on concrete, stucco, gypsum, gypsum boards, drywall, walls, ceilings, and trim of primed plaster, wallboard, wood, masonry, and primed metal.

**SYLPYL 750 DECORPLASTIC HBE Primer**, is a very versatile high build economic acrylic primer. Special for interior and exterior walls, ceilings and exterior of buildings in general. In new surfaces apply first one coat of our primer-sealer. VOC compliant with less than 50 grams per litre.

## PRODUCT SPECIFICATIONS

**PRODUCT:** SYLPYL 750 HBE HIGH BUILD PRIMER & SEALER

**TYPE:** Acrylic.

**COLOR:** Flat White

**FINISH:** Flat 5 units @ 85°

**SOLIDS BY VOLUME %:** 40 ± 2%

**WEIGHT SOLIDS:** 54 ± 2%

**WEIGHT PER GALLON:** 10 ± 2 lbs

**VISCOSITY:** 90-120 KU

**DENSITY:** 1.11-1.31 G/ML

**FLASH POINT:** N.A

**WASH ABILITY:** More than 12,000 cycles.

**THEORETICAL COVERAGE:** 390-405 sq.ft. per gallon @ 4 mils wet 1.7 mils dry.

**PRACTICAL COVERAGE IN SQUARE FEET PER GALLON:** 350-365 average.

This coverage can be less, depending on the roughness of the surface and the method of application.

### COVERAGE GUIDE:

TYPE OF SURFACE	FINAL THICKNESS 2 COATS
Smooth	400-460 ft <sup>2</sup> per gallon
Textured	340-390 ft <sup>2</sup> per gallon
Rough	240-320 ft <sup>2</sup> per gallon

\*Depending the color tone and type of surface

**V.O.C. (less exempt solvents):** 38.8 grams per litre; 0.34 lbs. per gallon  
As per 40 CFR 47.52. VOC compliant with less than 50 grams per Litre.

**NUMBER OF COATS RECOMMENDED:** ONE

**OVER POROUS SURFACES SUCH AS CONCRETE:** We recommend to apply one or 2 coats of **SYLPYL 750 LINE HBE PRIMER** (syl 78) primer-sealer to improve coverage.

Allow new concrete to cure a minimum of 28 days.

**THINNER:** Clean water. Max 10%.

**DRYING TIME AT 77°F (25°C), 50% RH:**

**TO TOUCH:** 60 Minutes

**HARD:** 90 Minutes

**TO RECOAT:** 4 Hours

Drying and recoat times are humidity, temperature, and film thickness dependent.

**SURFACE PREPARATION:** Fill cracks, pits and voids with patching Mortar. Remove dirt, grease, mildew, loose rust, peeling paint or other contamination to ensure good adhesion. Glossy surfaces: Lightly sand to a dull finish. Unpainted plasterboard, brick, cement: Apply one coat of Syl HBE PRIMER, water based all-in-one Vinyl Acrylic interior/exterior primer/sealer/undercoat with excellent hiding power. Surface must be dry.

**APPLICATION METHOD:** Roller, brush, conventional spray and airless.

**SHELF LIFE AT 77°F (25°C):** Minimum 36 months in unopened containers. Inside proper fresh warehouses.

**PACKAGING:** 1 gallon, 5 gallon and 250 gallons totes.

1 Liter=0.264 US gallon square meter=10.7639 square feet

THE RECOMMENDATIONS MADE HEREWITH AND THE INFORMATION SET FORTH WITH RESPECT TO THE PERFORMANCE OR USE OF OUR PRODUCTS ARE BASED ON OUR OWN RESEARCH, FROM LABORATORY TESTS WHICH ARE BELIEVED, BUT NOT WARRANTED, TO BE ACCURATE. THE PRODUCTS DESCRIBED ARE SOLD, WITHOUT WARRANTY, AS TO FITNESS OF PERFORMANCE, EXPRESSED OR IMPLIED, AND UPON CONDITION THAT PURCHASERS SHALL MAKE THEIR OWN TESTS TO DETERMINE THE SUITABILITY OF SUCH PRODUCTS FOR THEIR PARTICULAR PURPOSES. LIKEWISE, STATEMENTS CONCERNING THE POSSIBLE USES OF OUR PRODUCTS ARE NOT INTENDED AS RECOMMENDATIONS TO USE OUR PRODUCTS IN THE INFRINGEMENT OF ANY PATENTS OR THE INDOSEMENT OF PRODUCTS OF SPECIFIC MANUFACTURERS. WE DO NOT ASSUME ANY LIABILITY OR RESPONSIBILITY OF THE PRODUCT RELATIVE TO COVERAGE, PERFORMANCE, INJURY OR DAMAGE RESULTING FROM ITS USE. PRODUCT INFORMATION MAY CHANGE WITHOUT PREVIOUS NOTICE.

3208 Industrial 31<sup>st</sup> St, Fort Pierce, Florida 34946 USA Phone: (321) 398-0966

E-mail: [sales@sylypyl-usa.com](mailto:sales@sylypyl-usa.com) Visit us: [www.sylypyl.com](http://www.sylypyl.com) Certified Company ISO 9001-2015 & ISO 14001-2015